

## DATASHEET

# ArcLight NIR & IR lamps

## Stabilized Broadband Light Sources for VIS-NIR and IR

The Arcoptix ArcLight NIR & IR are versatile lamps optimized for the VIS-NIR (400 nm – 4,000 nm) or MIR (1-25 $\mu$ m) spectral ranges. The lamps feature an electronically stabilized power supply, a variable mechanical attenuator, and are supplied with a removable fiber coupler enabling free-space of fiber-coupled operation.



### ■ Features

- Near- and Mid-infrared versions available (0.4-4 $\mu$ m or 1-25 $\mu$ m)
- Electronically stabilized
- Brightest available lamps
- With mechanical intensity attenuator
- Free-space or fiber-coupled operation (removable fiber coupler)

## DATASHEET

### Specifications

Models	ArcLight-NIR	ArcLight-MIR
Lamp type	QTH (halogen)	SiC globar
Spectral Range [ $\mu\text{m}$ ]	0.4-4	1-25
Spectral Range [ $\text{cm}^{-1}$ ]	25,000-2,500	10,000 - 400
Temperature [K]	~2,850	~1,400
Rated Lifetime [hours]	4,000	10,000
Removable fiber-optic coupler	NA = 0.25 CaF2 lens	NA = 0.3 gold-coated off-axis parabolic mirror
Lamp electrical power [W]	20	
Output beam diameter [mm]	12.7mm	
Operational temperature range [ $^{\circ}\text{C}$ ]	5-40	
Attenuator	Manual iris diaphragm	
Power requirement	12V via OD2.5mm/ID2.1mm power jack (100-240V AC to 12V DC converter included)	
Dimensions	92mm x 92mm x 43mm (without fiber coupler) 140mm x 92mm x 43mm (with fiber coupler)	
Weight	390 g	

SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT NOTICE

Please contact [info@arcoptix.com](mailto:info@arcoptix.com) for more information.